



ProCore® Processor

CULTIVATION EQUIPMENT

FEATURES

- OnePass™ Hitch for tandem aeration and core processing
- 70" processing width
- Optional windrow kit for OnePass operation with aerators larger than 70"
- Carbide chopper blade tips
- Full-width rear roller
- Optional offset tow hitch option



Long-lasting carbide chopper blade tips perform exceptionally well in a variety of soil types

Stress relief for you and your turf.

Core aeration is vital to your turf's health, but highly disruptive to your staff and your operation. Fortunately, the ProCore Processor makes quick work core aeration clean up, helping to return your turf to play much faster and easier. It sweeps and pulverizes the aeration cores before returning the material back to the turf canopy. For even faster return to play, the optional OnePass hitch mounts the ProCore Processor behind your aerator allowing you to aerate and process cores in one pass.

The ProCore Processor reduces the total aeration time, allowing you to aerate more often to create healthy, robust turf.

toro.com/cultivation



Tractor-mount OnePass™ hitch for inline processing



Optional offset trailer hitch for utility vehicle processing



ProCore® Processor Specifications

PROCORE PROCESSOR, MODEL 09749	
ENGINE	Briggs & Stratton® Vanguard® 2 cylinder air-cooled 35 HP Gross, 31 HP Net, 993 cc displacement. High filtration replaceable element air filter. External spin on oil filter.
FUEL CAPACITY	10 gallons / 37.9 liters
PROCESSING WIDTH	70 inches / 178 cm
PROCESSING SYSTEM	Belt driven nylon brush sweeps material into chopper assembly equipped with carbide tips.
OPERATING SPEED	0-5 mph / 0-8 kmh
ROLLER	6" (15.2 cm) diameter full width rear roller.
CONSTRUCTION	Welded steel frame
HITCH SYSTEMS	Exclusive OnePass hitch allows attachment directly behind 3-point aerator. Offset tow hitch allows attachment to heavy duty work vehicle or tractor.
CONTROLS	Engine mounted key switch, choke and throttle. Remote mounted kill switch and offset control.
TRANSPORT TIRES	6-ply, 18 x 9.5 - 8
OVERALL WIDTH	88 inches / 224 cm
HEIGHT	44 inches / 112 cm
LENGTH	133 inches / 338 cm with OnePass hitch (09753), 170 inches / 432 cm with Tow Hitch (09750)
WEIGHT	2200 lbs / 998 kg
OPTIONS	Rear Wheel Kit (09768), Windrow Kit (09760), SMV (Slow Moving Vehicle) Kit
CERTIFICATION	ANSI B71.4-2004, OSHA, CE and EU machinery directives
WARRANTY	Two-year or 500-hour limited warranty. Refer to Operator's Manual for further details

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

